



GENERAL

WARRANTY: 1 year.
EFFECTIVE IN SPACES BETWEEN: 100-300m³.
ACTUATION METHOD: Continuous ventilation system.

AMBIANCE

TEMPERATURE RANGE: 10/70°C.
HUMIDITY RANGE: 15-93%.

ODOR ELIMINATOR TOWER

MOUNTING: Standing, screwed to the wall, or using double-sided adhesive tape.
NET WEIGHT: 700g.
DIMENSIONS: 93 x 93 x 300mm / 3,66 x 3,66 x 11,81inch.
MATERIAL: Galvanized sheet metal and aluminum.
COLORS: Black base and silver casing.
POWER: 3,36W a 12V.
SOUND LEVEL: 36 dB (A).
CONNECTION CABLE: Yes.
MARKETING: Can be customized with logo.

REFILL

CHARACTERISTICS: Odor eliminator through contact with air.
DURATION: 30 days.
MATERIAL: Probio Polymer.

HOW TO USE

1. Insert the polymers into the indicated cavity.
2. Connect the device using the power cable and it will start operating automatically.
3. To stop the operation, disconnect the device from the power outlet.

AVAILABLE REFILL

- Probio polymer bad odor eliminator.
- Probio polymer bad odor eliminator tobacco.

Register N.0: AN-04-DM-01
Version: 001
Date: 30 / 10 / 2025